

Company Introduction



Bröwiner

Digital Radiography System for Veterinary



Bröwiner

Shenzhen Browiner Tech Co., Ltd, established in January 2012 and located in Shenzhen city, China. We are a high-tech company specialized in Research, Manufacture, Sales and Service of Mobile Digital Radiography System.

We concentrate to create professional mobile medical imaging products, focus on new products research and development, popularization and application of mobile radiography technology. Browiner developed the most influential mobile DR system, portable DR system, pet DR system, we also focus on the research and the development of mobile dynamic radiography technology.

Browiner always commits to high technology and quality. It is our mission to protect human's health.

VX200/VX400

Floor-mounted Veterinary X-ray System



- ◆ High-power frequency generator, imported tube, amorphous silicon flat panel detector, and high performance image chain, ensures excellent images with low dose.
- ◆ High-power frequency generator, imported tube, amorphous silicon flat panel detector, and high performance image chain, ensures excellent images with low dose.

VX200/VX400

Floor-mounted Veterinary X-ray System

Main Component		Technical Specification	
Model		VX200	VX400
Flat Panel Detector	X-ray Sensitive Area	14x17inch	17x17inch
	Standard Power	20kW	32kW
Generator	kV Range	40-150kV	40-150kV
	mA Range	10-200mA	10-400mA
	mAs Range	0.1-80mAs	0.1-100mAs
X-ray Tube	Anode Heat Content	140kHU	200kHU
Physical Specification	Table Surface	121x61cm (L.W)	121x61cm (L.W)
	Table Movement Range	Horizontal:20cm Longitudinal:10cm	Horizontal:20cm Longitudinal:10cm
	Physical Dimension	120x87.5x200cm (L.W.H)	120x87.5x200cm (L.W.H)
Digital image workstation			
Processor	Intel Core 3 and above		
Memory capacity	4GB		
Hard drive capacity	500 GB		
Resolution	1920 x 1080		
Display size	24 inch color touch screen		
Operating system	Microsoft Windows 7 or above		
Option	Head Touchn Screen Workstation		

Additional: The models VX200(A) and VX400(A) are pet analogue X-ray system.

MobileCooper-Vet

Mobile Veterinary X-ray System



- ◆ High-index imaging chain, DC & AC working mode, cost-effective.
- ◆ Advanced folded design helps MobileCooper to achieve all-round rotation, compact structure and easy maintenance. Large angle arm design and high SID, meet different imaging position request.

MobileCooper-Vet

Mobile Veterinary X-ray System

Main Component		Technical Specification			Physical Specification		
Generator	X-ray Tube	Flat Panel Detector	X-ray Sensitive Area	14x17inch	Weight	220kg	
		Standard Power	40kW	Height	149cm		
			KV Range	40-150KV	Width	65cm	
mA Range	10-500mA	Tube Tilting Angle	±90°				
mAs Range	0.1-250mAs	Tube Vertical Rotation Angle	-30°~+90°				
Lithium Battery	Battery Capacity	46.8V, 10.8Ah	SID	507-2000mm			
	Anode Heat Content	150kHU	Arm's Folding Range	±60°			

Beagle-05VB-S

Portable Veterinary X-ray System



- ◆ 5.6kW high power generator, meets thick position demand.
Large capacity lithium battery ensures long standby and multiple exposure.
- ◆ Touch screen interface with APR setting, makes more easily operation.
Wireless flat panel detector and computer workstation, makes freely position.
Integrated suitcase package is easy to transport and carry.

Beagle-05VB-S

Portable Veterinary X-ray System

Main Component		Technical Specification			Physical Specification		
Generator	Flat Panel Detector	X-ray Sensitive Area	10x12/14x17inch	Main Unit	Weight	18kg	
	X-ray Tube	Standard Power	5.6kW		Stand	Dimension	44x24x23.6cm(LxWxH)
		KVp Range	40-125kVp			Weight	35kg
Collimator	Inherent Filtration	mA Range	10-100mA	Trolley Case	Maximum Expansion	100x75x210cm(LxWxH)	
		mA Range	0.1-200mA		Lithium Battery	Fold Dimension	105x40x40cm(LxWxH)
Touch Screen	Anode Heat Content	42KHU	8 inch	Battery Capacity		Dimension	106x50x50cm(LxWxH)
	Weight	19kg			Weight	32.4V, 5.4Ah	

Beatle-05VN-T

Integrated Veterinary X-ray System



- ◆ Integrated design, high power, small size. AC&DC power supply, meets multi-application scenes of radiography.
- ◆ Touch screen operation makes visual more intuitive. Lithium battery, fast charging, high efficiency, light weight. (option)

This brochure also applies to MobileSparker 300 A/B/C, MobileGenius A and MobileGenius B. It includes both standard & optional configuration, we do not guarantee that the optional configuration would be included in the product of your choice.



Bröwiner	Shenzhen Browiner Tech Co.,Ltd	
	Tel: +86 755-22674696 Website: www.browiner.com	Fax: +86 755-22674695 Email: market@browiner.com
	Add: 7 Floor, Building C, Longjing Jingu Pioneer Park, Longzhu 4th Road, Nanshan District, Shenzhen 518055, P.R.China	

Ver:201812V02